

The steel working company

Hydracrop 55

Where production requires twin operator machines, higher speeds or greater capacity, **GEKA** provides the solution with the **HYDRACROP** range with five working stations: punching, notching, shearing of flat bars, angles and Ø and Ø bars.

HYDRACROP 55	
SHEAR FOR FLAT BARS	
Shearing capacity	300x15 / 200x20 mm
Length of blades	305 mm
Working height	880 mm
SHEAR FOR SECTION IRON	
Shearing capacity	1100 Kn
L at 90 °	120x120x10
L at 45	70x70x7
SHEAR FOR BARS	
Round bar $arnothing$	40 mm
Square bar 🛛	40 mm
WITH SPECIAL BLADES	
UPN Profiles	120 mm
IPN Profiles	120 mm
NOTCHING	
Plate thickness	10 mm
Depth	90 mm
Width	42 mm
PUNCHING	
Punching power	550 Kn
Maximum capacity with quick change	Ø40x10
and die with gooseneck die holder	Ø20x20





Punching station

The punching station is fitted with an independent cylinder that creates a large, flexible, universal workstation easily adaptable for mounting special tools and "die sets".



Cylinder support



HI .

Limit switches for punch travel setting

Generous travel for bending, deep-drawing, forming jobs etc

Split double acting cylinder



Adjustable generous non-turning guiding

Additional guiding for damping of offset forces and protection of hydraulic seals

Spindle for fitting of special tools

Quick punch change

Adjustable material stripper

Table with millimetre scales, included in production package

Adjustable measuring stop up to 500 mm

Gooseneck die-holder for punching channel and section

Adjustable bolster locking device X axis




Fixing bolt at base of gooseneck

L cutting angle


Fully aware of the importance of distortion free shearing, GEKA has designed a patented system of a floating upper blade that travels along a rectilinear line and is able to shear angles without any deformation and loss of material (single cut); All GEKA Hydracrop models ensure that distortion problems caused by the conventional radial system are now a problem of the past.



Adjustable Support



Upper shear blade without deformation




Safety protection

Shearing for flat bars

The excellent stability of the monoblock blade-holder, which is controlled at the each end, makes it possible to mount a long upper blade with a proven geometry to obtain optimum shearing quality. The radial system allows a generous cutting capacity as a result of the force multiplier effect.

- 1. Lower blade
- 2. Upper blade with special geometry
- 3. Clearance control between shear blades
- 4. Supplement shearing angle control of upper blade, for shearing without deformation.
- 5. Adjustable guides 45° right and left.
- 6. Flat plate/bar shearing table.
- 7. Slotted guide positioning with coverage of the entire blade length
- 8. Guide fixing screw
- 9. Clearance control of blade-holder



lade guides

Hydracrop 55

Notching station



Guide fixing bolts



- World leader in punching and shearing solutions
- Worldwide distribution network
- Proven quality, design and craftsmanship
- Continuous innovation
- Complete after sales service
- Great versatility that includes the highest range in accessories and optional equipments in the market
- The only machine fully produced and manufactured in the European Union
- All GEKA machines are special order. GEKA is the only ironworker that you can customize to fit your needs

www.geka.es

Distributor